

## technická data



### ÚVAZKY

	velikost	UNI	K1	K2	XS	S	M	L	XL	XXL	norma	CE
<b>ONYX</b> C5059	(M) 340 g A cm B cm in in				65-75 25,5-29,5 49 19	70-80 27,5-31,5 52 20	75-85 29,5-33,5 55 21	80-90 31,5-35,5 58 22	85-95 33,5-37,5 60 23		EN 12277	CE 1019
<b>PEARL</b> C5061	(M) 390 g A cm B cm in in				60-70 23,5-27,5 50-55 19,5-21,5	65-75 25,5-29,5 50-55 19,5-21,5	70-80 27,5-31,5 55-60 21,5-23,5	75-85 29,5-33,5 60-65 23,5-25,5	80-90 31,5-35,5 65-70 25,5-27,5		EN 12277	CE 1019
<b>SPINEL</b> C5062	(M) 450 g A cm B cm in in					65-80 25,5-31,5 50-55 19,5-21,5	75-90 29,5-35,5 60-65 23,5-25,5		85-100 33,5-39,5 65-70 25,5-27,5		EN 12277	CE 1019
<b>GARNET</b> C5060 C5064	(M) 400 g A cm B cm in in				65-75 25,5-29,5 50-55 19,5-21,5	70-80 27,5-31,5 50-55 19,5-21,5	75-85 29,5-33,5 55-60 21,5-23,5	80-90 31,5-35,5 60-65 23,5-25,5	85-95 33,5-37,5 65-70 25,5-27,5	90-100 35,5-39,5 65-70 25,5-27,5	EN 12277	CE 1019
<b>ARA</b> C5063XAD1 C5063XAD2	(K1) 280 g A cm B cm in in		55-65 19,5-23,5 35-40 14-17,5	60-70 21,5-25,5 40-45 17,5-19,5							EN 12277	CE 1019
<b>DOVE</b> C5017	(S/M/L) 560 g A cm B cm in in					55-80 22-31 45-58 18-23	60-95 23-37 44-62 17-24		70-120 23-47 44-72 17-28		EN 12277	CE 1019
<b>VERSA</b> C5048	(XS-M) 420 g A cm B cm in in				63-90 25-35,5 45-58 18-23			75-102 29,5-40 55-68 21,5-26,5			EN 12277	CE 1019
<b>ATTACK III</b> C5037	(M) 400 g A cm B cm in in				65-75 25,5-29,5 45-50 17,5-19,5	70-80 27,5-31,5 50-55 19,5-21,5	75-85 29,5-33,5 55-60 21,5-23,5	80-90 31,5-35,5 60-65 23,5-25,5	85-95 33,5-37,5 65-70 25,5-27,5	90-100 35,5-39,5 65-70 25,5-27,5	EN 12277	CE 1019
<b>FLAKE</b> C50455	(M/L) 240 g A cm B cm in in					65-80 25,5-31,5 50-55 19,5-21,5	75-90 29,5-35,5 60-65 23,5-25,5	75-90 29,5-35,5 60-65 23,5-25,5	85-100 33,5-39,5 65-70 25,5-27,5		EN 12277	CE 1019
<b>RAY</b> C5038	(M) 390 g A cm B cm in in				65-75 25,5-29,5 45-50 17,5-19,5	70-80 27,5-31,5 50-55 19,5-21,5	75-85 29,5-33,5 55-60 21,5-23,5	80-90 31,5-35,5 60-65 23,5-25,5	85-95 33,5-37,5 65-70 25,5-27,5	90-100 35,5-39,5 65-70 25,5-27,5	EN 12277	CE 1019
<b>TOP</b> C5031BS	UNI 366 g A cm B cm in in	60-120 24-47 42-66 17-27									EN 12277	CE 1019
<b>TOP PADDED</b> C5032BS	UNI 402 g A cm B cm in in	60-120 24-47 42-66 17-27									EN 12277	CE 1019

## technická data



	velikost	UNI	XS	S	M/L	L	XL	norma	CE
<b>BRIO II</b> C5068BY00	(M) 480 g A cm B cm in in	UNI 60-116 24-46 42-72 17-23						EN 12277	CE 1019
<b>CANYON XP</b> C5030BS	(M/L) 614 g A cm B cm in in			70-100 28-40 42-66 17-27	80-110 32-43 42-66 17-27		90-120 36-48 42-66 17-27	EN 12277	CE 1019
<b>TOP CANYON</b> C5029BS	UNI 502 g A cm B cm in in	60-120 24-47 42-66 17-27						EN 12277	CE 1019
<b>DIGGER LIGHT</b> S0101Y800	UNI 520 g A cm B cm in in	max. 110 max. 43 50-80 20-31						EN 12277	CE 1019
<b>ALADIN</b> C5056	UNI 240 g D cm in in	75-110 30-43						EN 12277	CE 1019
<b>ALADIN PLUS</b> C5057	(UNI) 435 g D cm in in	75-110 30-43						EN 12277	CE 1019
<b>BALA</b> C5047	(UNI) 350 g C cm in in	95-130 37-49						EN 12277	CE 1019
<b>TARZAN</b> W0050BR	(M-XL) 1530 g A cm B cm C cm in in in		50-80 20-31 45-60 18-24 145-165 57-65	50-80 20-31 45-60 18-24 145-165 57-65	70-130 27-51 50-75 20-29 160-205 63-80		70-130 27-51 50-75 20-29 160-205 63-80	EN 358, 813, 361	CE 1019
<b>TARZAN LIGHT</b> C5036BR00	(UNI) 930 g A cm B cm C cm in in in	60-130 24-51 35-70 14-27 150-200 59-76						EN 12277	CE 1019
<b>COMPLETE</b> C0710	(UNI) 550 g C cm in in	140-200 17-27						EN 12277	CE 1019
<b>ROPE-DANCER II</b> W0087	(S/M/L) 1170 g C cm in in		130-155 51-61	150-185 59-73	150-185 59-73	180-210 71-83	180-210 71-83	EN 361, 813	CE 1019